

SAFETY DATA SHEET

HUMBROL- LIQUID POLY

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME HUMBROL- LIQUID POLY
APPLICATION Adhesive
SUPPLIER Colart Fine Art & Graphics Limited
Whitefriars Avenue
Harrow
Middlesex HA3 5RH
+44 (0) 208 4274343
44 (0) 208 42433217

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Butyl acetate	204-658-1	123-86-4	60-100%	R10,R66,R67.

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION R10, R66, R67.

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Get medical attention immediately! NOTE! Keep affected person away from heat, sparks and flames!

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Alcohol resistant foam. Carbon dioxide (CO2). Water spray, fog or mist. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

Ventilate closed spaces before entering them.

UNUSUAL FIRE & EXPLOSION HAZARDS

FLAMMABLE. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back. Solvent vapours may form explosive mixtures with air.

PROTECTIVE MEASURES IN FIRE

Wear full protective clothing.

6 ACCIDENTAL RELEASE MEASURES

HUMBROL- LIQUID POLY

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Flush with plenty of water to clean spillage area. Do not let washing down water contaminate ponds or waterways.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in closed original container in a dry place. Store in a cool and well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Wear approved safety goggles. Contact lenses should not be worn when working with this chemical!

OTHER PROTECTION

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes wet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
ODOUR	Solvent.		
SOLUBILITY	Slightly soluble in water.		
BOILING POINT (°C)	126 760 mm Hg	RELATIVE DENSITY	0.88 20.C
VAPOUR DENSITY (air=1)	4	VAPOUR PRESSURE	8 mm Hg 20. C
VOLATILE BY VOL. (%)	100	FLASH POINT (°C)	22. CC (Closed cup).
AUTO IGNITION	~420	FLAMMABILITY LIMIT - LOWER(%)	1.7
TEMPERATURE (°C)			
FLAMMABILITY LIMIT - UPPER(%)	7.6		

10 STABILITY AND REACTIVITY

HUMBROL- LIQUID POLY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with oxidisers or reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

Harmful by inhalation. Vapour from this chemical can be hazardous when inhaled. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication.

INGESTION

Harmful if swallowed. May cause stomach pain or vomiting.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact.

TARGET ORGANS

Mucous membranes. Central nervous system.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

There are no data on the ecotoxicity of this product.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	ADHESIVES		
UN NO. ROAD	1133	ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.	HAZARD No. (ADR)	30.
ADR LABEL NO.	3	HAZCHEM CODE	3[Y]
CEFIC TEC(R) NO.	30G35	RID CLASS NO.	3
UN NO. SEA	1133	IMDG CLASS	3.3
IMDG PACK GR.	III	UN NO. AIR	1133
AIR PACK GR.	III		

15 REGULATORY INFORMATION

RISK PHRASES

R10 Flammable.

HUMBROL- LIQUID POLY

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2 Keep out of the reach of children

S37 Wear suitable gloves.

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

S56 Dispose of this material and its container to hazardous or special waste collection point.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

16 OTHER INFORMATION

DATE 16/11/2007

RISK PHRASES IN FULL

R10 Flammable.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.